



INSTRUCTIONS FOR USE PERSONAL PROTECTIVE EQUIPMENT (P.P.E.)

Read these instructions carefully before using this clothing. Refer to your safety engineer or manager regarding the appropriate clothing for your specific work situation. Keep these instructions carefully so you can refer to them whenever you wish.

Declaration of conformity for this P.P.E. and more comprehensive instructions for use: see <http://sio.to/eudoc>



This item complies with the fundamental requirements of European Regulation 2016/425 on personal protective equipment (P.P.E.) based on European harmonised standard(s); **you will find corresponding pictograms and protection class on the label sewn into this garment.**

Except for clothing that is only labelled EN 343 or EN ISO 24232 and/or EN 14058 and/or EN 13758-2 (and is covered by self-certification, with exception of $R_{ct} > 0.25 \text{ m}^2 \text{ K/W}$), all our other P.P.E. covered by this manual has been certified by Centexbel, Technologiepark 70, B-9052 Zwijnaarde (Belgium) - NB 0493 or Total Testing Service, Rue de l'Echauffourée 1 CART B-7700 Mouscron - NB 2959 or Aitex, Carretera Banyeres n° 10, 03802 Alcoy (Spain) - NB 0161. (see declaration of conformity). If this number 0493 is shown on the right next to the CE pictogram on the label sewn into the garment, it means that it is category III P.P.E. of a complex design that is to protect the user against hazards which are fatal or which can seriously and irreparably impair one's health, and the quality assurance monitoring of the manufacturing process is carried out by Centexbel. You will find corresponding pictograms and protection classes on the label sewn into this garment.

This P.P.E. complies with General Standard EN ISO 13688 / EN ISO 13688:2013 + A1:2021. This P.P.E. complies with the REACH Regulation and does not contain any substances known at this time to cause allergic reactions or which are known to be carcinogenic or mutagenic. As with all P.P.E., this product does not protect you against all risks! Check your specific risk assessment.

This P.P.E. will also be worn combined with other P.P.E. (including non-clothing P.P.E.). Check the compatibility and correct use when combined with other P.P.E.. Read the manuals off

other P.P.E. as well.

With regard to protection against rain, cold, chemicals, fire, heat, etc. it is self-evident that you will only be protected on the parts of the body covered by the P.P.E. when performing activities and movements. As it is possible to combine different garments, you need to ensure that all parts of the body are covered with the appropriate levels of protection.

Making alterations to this clothing (without authorisation from Sioen) is not permitted! For optimum and compliant protection, you need to close all fasteners.

Never wear a damaged garment. A damaged garment must be taken out of use immediately and either repaired or replaced. Notify your manager at once. At 'end of life', this garment must be collected, removed and processed in controlled conditions (professional collection service for mechanical or thermal recycling, etc.) in a specialised facility.

We recommend professional care (via an in-house or external laundry). Specific care instructions for commercial laundries are available from Sioen upon request or on the Sioen website <http://sio.to/eudoc>. Care instructions for domestic laundering (which can also be done at a commercial laundry!) appear on the label sewn into the garment.

You will find a more detailed explanation of these symbols on the Sioen website <http://sio.to/eudoc>.

Please contact your Sioen dealer in all cases for more information about care instructions, repairs and safe destruction methods.

Label	Clarification
MAX	Maximum (theoretical) number of cleaning cycles means certification testing to be carried out after x cleaning cycles.
	Expiry date or 'do not use after' date.
	Certification tests carried out after an industrial laundry process (see http://sio.to/eudoc).
	The values entered in A, B, C are the corresponding body measurements (in cm) for which this garment is suitable. You will find the various sizing tables on our website see http://sio.to/eudoc . (A: Waist girth - B: Chest girth - C: Length)

Do not allow your garment to become too soiled. **Soiled clothing can result in reduced protection.** Chemicals (including their long-term effect due to clothing being put away soiled) can impair the protective properties of the clothing.

When picking up your clothing check that you have the right size and that there is no visible damage in evidence.

As a general rule, garments should be selected in such a way that the work can be carried out comfortably and unhindered.

Manufacturing traceability

The requisite details are shown at the bottom of the label.

Storage instructions

When you are not wearing the garment, you should store it dry, uncompressed, in a well-ventilated room. Avoid extreme temperatures and avoid direct sunlight to prevent colour changes. Complaints about colour changes will not be considered.

Sioen cannot be held liable for damage occurring as a result of improper use of the P.P.E. or any use that does not comply 100% with the instructions for use set out above.

Seasonal protective clothing - Protection against water



This pictogram **without** any mention of [EN 343](#) or [EN ISO 24232](#) standard indicates seasonal protective clothing (self-certification) with basic protection against light rain and drizzle and with seams which are not necessarily made waterproof.

EN ISO 20471:2013 +A1:2016

This clothing makes the user stand out where visibility is poor in high-risk situations



EN ISO 20471

The combination of a fluorescent base material with retroreflective strips signals your presence in daylight or in the dark (in the light from headlamps) respectively.

Protective clothing with reference HRVx

<u>x (See label)</u>	Fluorescent (m ²)	Retroreflective (m ²)
Class 1	≥ 0.14	≥ 0.10
Class 2	≥ 0.50	≥ 0.13
Class 3	≥ 0.80	≥ 0.20

The garment must be fully closed and must not be covered in order to ensure visibility.

Visibility is dependent on use (e.g. soiling, etc.) care (repairs, cleaning, etc.) and storage (to be stored preferably in a dark environment). The maximum permissible number of care cycles is shown on the label as 'Max xx' (this is an indication of the number of laundry

cycles after which certification has been carried out) but this is not the only factor that will determine the lifespan of the garment. The lifespan will also depend on use, care, storage conditions, etc. Caution is advised when laundering together with other dark garments (risk of colourstaining). After exposure to light, the colour may fall in a different colour area from the original, however the colour will then still comply with EN ISO 20471.

For P.P.E. with removable sleeves its class may (will) be lower with the sleeves unzipped (see label). A sleeveless EN ISO 20471 Class 3 garment must be combined with a garment which has long sleeves and/or long trouser legs with 2 retroreflective strips 5 cm wide and a minimum of 5 cm of fluorescence all around the sleeves and/or trouser legs respectively.

EN ISO 20471 - Except § 5.6

This clothing provides the user protection against insignificant visibility by means of conspicuous materials, in accordance with EN ISO 20471:2013+A1:2016, with the exception of §5.6. - Physiological performance - Water vapour and thermal resistance. The garment has restricted wearingtime



This garment does not comply with clause 5.6 of the standard EN ISO 20471:2013+A1:2016, which meets minimum performance to physiological performances such as water vapour and thermal resistance. Therefore, the clothing has a limited wearing time. A recommendation is added in the clothing "Restricted wearing time". The following table is a guide to illustrate the effect of water vapour permeability on the recommended continuous wearing time of a garment in different ambient temperatures.

Temperature of working environment (°C)	25	20	15	10	5
Recommended max continuous wearing time (min.)	60	75	100	240	NA

Seasonal protective clothing - Thermal protection

This pictogram **without** any mention of EN 14058 standard indicates seasonal protective clothing (self-certification) with a basic thermal lining that is to be used in an environment with humidity and windchill (for mild cold, temperatures above -5°C).



EN 14058:2017 / EN 14058:2017+A1:2023

Protection against cool environments (possible combination of humidity and wind at temperatures not lower than -5°C)



Protective clothing with reference LC a, b, c, d

- a Thermal resistance R_{ct} measured on fabric combination: class 1 to 4. (see label)
- b Optional: air permeability class: classes 1 to 3. (see label)
- c Optional for a = 1, 2 or 3: resultant effective thermal insulation value I_{cler}

(in $\text{m}^2 \cdot \text{K/W}$), measured dynamically on clothing combined with type R underclothing item code (see label for value).

- d Optional: resistance to water penetration > 0.8 m water column.

An 'X' on the label means that this optional property has not been tested.

	a: Rct ($\text{m}^2 \text{ K/W}$)	b: Air permeability AP (mm/s)
Class 1	$0.06 \leq \text{Rct} < 0.12$	$100 < \text{AP}$
Class 2	$0.12 \leq \text{Rct} < 0.18$	$5 < \text{AP} \leq 100$
Class 3	$0.18 \leq \text{Rct} < 0.25$	$\text{AP} \leq 5$
Class 4	$0.25 \leq \text{Rct}$	/

For the intended field of use of classes 1 to 4 inclusive, see tables on Sioen website:
<http://sio.to/eudoc>

Thermal insulation can decrease after laundering or due to compression. This garment protects only those parts of the body that are covered by the garment. For complete protection, the entire body including arms and legs needs to be covered. A bodywarmer or waistcoat only provides supplementary protection.

EN 13758-2:2003 +A1:2006

Protects the user against UV radiation (UVA + UVB) from the sun



EN 13758- 2

Protective clothing with reference UPF

UPF (ultraviolet protection factor) must be at least 40 and is to be measured in accordance with [EN 13758-1](#). This clothing only protects the parts of the body which are covered. Exposure to the sun for long periods can cause serious damage to your skin. Accordingly, use a high-factor sun cream on parts not covered. The protective factor of this clothing can be reduced through use, when taking it off or when wet.

EN 14404-3:2024

Personal protective equipment - knee protectors for work in the kneeling position (type 2)



EN 14404-3:2024

This personal protective equipment (trousers + knee protector) will protect

the knees of the wearers when the wearers regularly must kneel to perform their work. It will minimize the risk of injury and chronic discomfort caused by continuous pressure on the knees when working in a kneeling position. The selection and use of the correct PPE shall be based on a risk assessment of the conditions in which the wearer will be working.

To protect the wearer, the kneepad shall be correctly put in the knee pockets of the workwear trousers. When standing, the kneepads in the trousers shall be just below the knee-caps. The certification is only valid for the combination of the kneepad and workwear

trousers as mentioned on the trousers' label. In case the EN 14404-3:2024 indication and the kneepad indication are not present of the trousers' label, the trousers are not intended for use in combination with knee protectors.

Reference Kneepad	Indication kneepad
DISKOS - 001MA2ZZP Size: Large (indicated as 'L' on the kneepad) Composition: polyolefin foam with addition of EVA fabric with Cordura fabric (high tenacity PA 66) Measurements: Length= 240 mm Width= 150 mm Thickness = 20 mm	 001MA2ZZP Logo as shown on the label of a compatible garment

Type 2 kneepads are protectors placed in kneepad pockets on trousers.

- **Level 0** knee protectors providing no protection against penetration and with a force distribution less than 30 N when tested on flat surface.
- **Level 1** knee protectors providing protection against penetration at a force of at least 100 N and with a force distribution less than 30 N when tested on flat even surface.
- **Level 1U** knee protectors providing protection against penetration at a force of at least 100 N and a force distribution less than 30 N when tested on uneven surface.
- **Level 2** knee protectors providing protection against penetration at a force of at least 250 N and with a force distribution less than 30 N when tested on uneven surface.

On the kneepad is clearly indicated the top side and the side that should be towards the knee.

The kneepads are not intended for use in contact with solvents and are not water resistant. The kneepads can be impaired in extreme hot or cold environments. Keep the kneepads away from heat and fire. The kneepads shall be removed from the trousers before washing. The kneepads can be wiped with a damp cloth.

No protector can offer full protection against injuries. Care should always be taken to limit the time spent in kneeling position to prevent repetitive strain injuries. Always seek medical advice when experiencing problems.

The kneepads shall be visually inspected regularly. When there is dirt, permanent contamination, embrittlement, damage or wear, or the kneepad is altered, this can severely undermine the protection performance. When a kneepad is worn/damaged/compressed, both kneepads shall be discarded immediately and replaced by new kneepads of the exact same type.



This personal protective equipment (trousers + knee protector) will protect the knees of the wearers when the wearers regularly must kneel to perform their work. It will minimize the risk of injury and chronic discomfort caused by continuous pressure on the knees when working in a kneeling position. The selection and use of the correct PPE shall be based on a risk assessment of the conditions in which the wearer will be working.

To protect the wearer, the kneepad shall be correctly put in the knee pockets of the workwear trousers. When standing, the kneepads in the trousers shall be just below the knee-caps. The certification is only valid for the combination of the kneepad with the workwear trousers as mentioned on the trousers' label. In case the EN 14404:2004+A1:2010 indication and the kneepad indication are not present of the trousers' label, the trousers are not intended for use in combination with knee protectors.

Reference Kneepad	Type and level
JEROM - 001WA2ZZQ Size kneepad: one size fits all Composition: 100 % EVA foam Measurements: Length= 240 mm Width= 140 mm Thickness = 22 mm	 1 Type 2 level 1

Type 2 kneepads are protectors placed in kneepad pockets on trousers.

- **Level 0** knee protectors suitable only for use on flat surfaces and providing no protection against penetration.
- **Level 1** knee protectors suitable for use on flat or non-flat floor surfaces and providing protection against penetration at a low force ($\geq 100 \pm 5$ N).
- **Level 2** knee protectors suitable for use on flat or non-flat floor surfaces in severe conditions and providing protection against penetration at a medium force ($\geq 250 \pm 10$ N).

On the kneepad is clearly indicated the top side and the side that should be towards the knee.

The kneepads are not intended for use in contact with solvents and are not water resistant. The kneepads can be impaired in extreme hot or cold environments. Keep the kneepads away from heat and fire. The kneepads shall be removed from the trousers before washing. The kneepads can be wiped with a damp cloth.

No protector can offer full protection against injuries. Care should always be taken to limit the time spent in kneeling position to prevent repetitive strain injuries. Always seek medical advice when experiencing problems.

The kneepads shall be visually inspected regularly. When there is dirt, permanent contamination, embrittlement, damage or wear, or the kneepad is altered, this can severely undermine the protection performance. When a kneepad is worn/damaged/compressed, both kneepads shall be discarded immediately and replaced by new kneepads of the exact same type.

EN 510:2019

Risk of entanglement with moving parts



EN 510

Protective clothing with RO item code

Protective clothing that reduces the risk of entanglement with moving machinery - or parts thereof - for wearers who work in the vicinity of machinery or equipment with hazardous moving parts.

With a 2-piece P.P.E. suit, it requires to be worn together and there must be no gaps occurring between the jacket and trousers as a result of body movements. This clothing must be worn as far as possible fitted/close to the body and be closed completely.

Clothing capable of signaling the user's presence visually

This clothing does not meet the requirements and is not in accordance with [EN ISO 20471](#).



EN 17353:2020 (+A1:2025)

This clothing makes the user stand out where visibility is poor in medium-risk situations

		
EN 17353	EN 17353	EN 17353
Type A	Type B	Type AB

This clothing is intended for medium risk situations depending on the task related risk analysis: significantly reduced traffic speeds (≤ 60 km/hr active road users or ≤ 15 km/hr for passive road users) and/or reduced traffic density. It is not intended for high-risk situations which are covered by [EN ISO 20471](#).

The presence of a fluorescent base material and/or retroreflective strips signals your presence in daylight or in the dark (in the light from headlamps) respectively.

Protective clothing with reference MRVx

x (See label)	type	Fluorescent (m ²)	Retroreflective (m ²)	Combined material (m ²)
Type B2	Dark conditions - limbs	/	≥ 0.018	/

Type B3	Dark conditions - on torso or torso and limbs	/	$\geq 0.08^*$	/
Type A	Daylight	$\geq 0.24^*$	/	/
Type AB	Daylight, twilight and dark conditions	$\geq 0.24^*$	$\geq 0.08^*$ For version 2020+A1:2025: AB2: $\geq 0.018^*$ AB3: $\geq 0.08^*$	$\geq 0.24^*$

(*) For height > 140 cm

For type B2 and B3 clothing, when small elements of hi-vis colours are present, these are only for decorative design purposes and do not give you day visibility. For type A, when small reflective elements are present, these are only for decorative design purposes and do not give you night visibility.

When the standard EN 17353 is not indicated on the label, but there are small fluo or reflective elements on the style, these are only for decorative design purposes and do not give you day and/or night visibility.

The garment must be fully closed and must not be covered in order to ensure visibility.

When wearing partial body protective clothing such as aprons, chaps, the visibility from all sides can depend on the size of the wearer as these models are mostly uni-size (see label). The girth of the wearer has an influence on the distribution of the visibility, the larger the girth the less visibility on the back (apron, chaps).

Visibility is dependent on use (e.g. soiling, etc.) care (repairs, cleaning, etc.) and storage (to be stored preferably in a dark environment). The maximum permissible number of care cycles is shown on the label as 'Max xx' (this is an indication of the number of laundry cycles after which certification has been carried out) but this is not the only factor that will determine the lifespan of the garment. The lifespan will also depend on use, care, storage conditions, etc. Caution is advised when laundering together with other dark garments (risk of colourstaining). Wash together with similar colours. Any alterations of the product such as printing of logos may compromise the minimum areas and performance of the product. After exposure to light, the colour may fall in a different colour area from the original, however the colour will then still comply with [EN 17353](#).



The knee pockets are not intended for knee protection according to EN 14404 for prolonged kneeling work, but only for comfort and durability and they may not be used for inserting knee protectors according to EN 14404.

SIOEN

Manufacturer:

Sioen nv, Fabriekstraat 23, B-8850 Ardooie, Belgium

T: +32 (0)51 740 800 • www.sioen.com



Importer UK: Sioen UK

Altham Lane, Altham, Accrington, Lancashire BB5 5YA, UK



FR

PAPIER



Recycle



Raccolta differenziata,
verifica le disposizioni
del tuo comune

SIOEN | VERSION 09-06-2026