# Характеристики




**Фото репрезентативне**



## Eaton 286513

Eaton Moeller series xPole - PF6/7 RCCB. PF6, 4 pole, In: 63 A, Icn: 6 kA, IΔN: 0.1 A, Type AC, AC current sensitive, Partly surge-proof 250 A, residential and commercial

### Загальні характеристики

| | |
|---|---|
| **PRODUCT NAME** | Eaton Moeller series xPole - PF6/7 RCCB |
| **CATALOG NUMBER** | 286513 |
| **EAN** | 4015082865139 |
| **PRODUCT LENGTH/DEPTH** | 76 mm |
| **PRODUCT HEIGHT** | 80 mm |
| **PRODUCT WIDTH** | 70 mm |
| **PRODUCT WEIGHT** | 0.32 kg |
| **COMPLIANCES** | RoHS conform |
| **CERTIFICATIONS** | IEC/EN 61008 |
| **MODEL CODE** | PF6-63/4/01 |

Powering Business Worldwide

## Характеристики продукту

| | |
|---|---|
| **USED WITH** | KLV-TC-4 276241 (Compact enclosure)<br>Z-FW/LP 248296 (Remote control and automatic switching device)<br>Z-RC/AK-4TE 101062 (sealing cover set) |
| **AMPERAGE RATING** | 63 A |
| **VOLTAGE RATING** | 230 V AC / 400 V AC |
| **FEATURES** | Additional equipment possible<br>Residual current circuit breaker |
| **ACCESSORIES REQUIRED** | Z-HK 248432 |
| **10.10 TEMPERATURE RISE** | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| **10.11 SHORT-CIRCUIT RATING** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.12 ELECTROMAGNETIC COMPATIBILITY** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.13 MECHANICAL FUNCTION** | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| **10.2.2 CORROSION RESISTANCE** | Meets the product standard's requirements. |
| **10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES** | Meets the product standard's requirements. |
| **10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT** | Meets the product standard's requirements. |
| **10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS** | Meets the product standard's requirements. |
| **10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION** | Meets the product standard's requirements. |

## Ресурси

| | |
|---|---|
| ІНСТРУКЦІЇ ЩОДО ВСТАНОВЛЕННЯ | eaton-mcb-rccb-rcbo-g9-il019140zu.pdf |
| КАТАЛОГИ | eaton-xpole-pf6-rccb-catalog-ca019034en-en-us.pdf<br>eaton-xpole-pf7-rccb-catalog-ca019032en-en-us.pdf |
| КРЕСЛЕННЯ | eaton-circuit-breaker-xeffect-frcmm-rccb-dimensions.jpg<br>eaton-xpole-pf67-rccb-3d-drawing.jpg |

| | |
|---|---|
| **10.2.5 LIFTING** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.2.6 MECHANICAL IMPACT** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.2.7 INSCRIPTIONS** | Meets the product standard's requirements. |
| **10.3 DEGREE OF PROTECTION OF ASSEMBLIES** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.4 CLEARANCES AND CREEPAGE DISTANCES** | Meets the product standard's requirements. |
| **10.5 PROTECTION AGAINST ELECTRIC SHOCK** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS** | Is the panel builder's responsibility. |
| **10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS** | Is the panel builder's responsibility. |
| **10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH** | Is the panel builder's responsibility. |
| **10.9.3 IMPULSE WITHSTAND VOLTAGE** | Is the panel builder's responsibility. |
| **10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL** | Is the panel builder's responsibility. |
| **FITTED WITH:** | Interlocking device<br>IS/SPE-1TE 101911 |
| **FRAME** | 45 mm |
| **FREQUENCY RATING** | 50 Hz |
| **POLLUTION DEGREE** | 2 |
| **LIFESPAN, MECHANICAL** | 20000 operations |
| **MOUNTING METHOD** | DIN rail<br>Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715 |
| **CLIMATIC PROOFING** | 25-55 °C / 90-95% relative humidity according to IEC 60068-2 |
| **EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT** | 10.5 W |
| **RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** | 4 kV |

| | |
|---|---|
| **RATED SHORT-TIME WITHSTAND CURRENT (ICW)** | 6 kA |
| **ADMISSIBLE BACK-UP FUSE OVERLOAD - MAX** | 40 A gG/gL |
| **BUILT-IN WIDTH (NUMBER OF UNITS)** | 70 mm (4 SU) |
| **BUSBAR MATERIAL THICKNESS** | 0.8 mm - 2 mm |
| **SHORT-CIRCUIT RATING** | 63 A (max. admissible back-up fuse) |
| **TERMINAL PROTECTION** | Finger and hand touch safe, DGUV VS3, EN 50274 |
| **TERMINALS (TOP AND BOTTOM)** | Open mouthed/lift terminals |
| **TEST CIRCUIT RANGE** | 184 V AC - 440 V AC |
| **AMBIENT OPERATING TEMPERATURE - MAX** | 60 °C |
| **AMBIENT OPERATING TEMPERATURE - MIN** | -25 °C |
| **BUILT-IN DEPTH** | 69.5 mm |
| **CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX** | 16 mm² |
| **CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN** | 1.5 mm² |
| **CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX** | 35 mm² |
| **CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN** | 1.5 mm² |
| **FAULT CURRENT RATING** | 100 mA |
| **HEAT DISSIPATION CAPACITY** | 0 W |
| **HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT** | 0 W |
| **PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MAX** | 60 °C |
| **PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MIN** | -35 °C |
| **DEGREE OF PROTECTION** | IP20, IP40 with suitable enclosure |

| | |
|---|---|
| | IP20 |
| **IMPULSE WITHSTAND CURRENT** | Partly surge-proof 250 A |
| **NUMBER OF POLES** | Four-pole |
| **LEAKAGE CURRENT TYPE** | AC |
| **LIFESPAN, ELECTRICAL** | 4000 operations |
| **TYPE** | • PF6<br>• Residual current circuit breakers<br>• Type AC |
| **SPECIAL FEATURES** | • Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 1.8% for every 1 °C<br>• Tripping signal contact for subsequent installation Z-NHK 248434 |
| **APPLICATION** | • Residual current circuit breaker for residential and commercial applications<br>• xPole - Switchgear for residential and commercial applications |
| **SENSITIVITY TYPE** | AC current sensitive |
| **RATED FAULT CURRENT - MAX** | 0.1 A |
| **RATED FAULT CURRENT - MIN** | 0.1 A |
| **RATED INSULATION VOLTAGE (UI)** | 440 V |
| **RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** | 63 A |
| **RATED OPERATIONAL VOLTAGE (UE) - MAX** | 400 V |
| **RATED RESIDUAL MAKING AND BREAKING CAPACITY** | 630 A |
| **STATIC HEAT** | 0 W |

| | |
|---|---|
| **DISSIPATION, NON-CURRENT-DEPENDENT** | |
| **SURGE CURRENT CAPACITY** | 0.25 kA |
| **WIDTH IN NUMBER OF MODULAR SPACINGS** | 4 |
| **VOLTAGE TYPE** | AC |
| **TERMINAL CAPACITY (SOLID WIRE)** | 1.5 mm² - 35 mm² |
| **TRIPPING TIME** | Non-delayed |
| **RATED SHORT-CIRCUIT STRENGTH** | 6 kA |
| **TERMINAL CAPACITY (STRANDED CABLE)** | 16 mm² (2x) |
| **RAL-NUMBER** | 7035 |
| **COLOR** | Gray |

| | |
|---|---|
| **НАЗВА ПРОЕКТУ:** | |
| **НОМЕР ПРОЕКТУ:** | |
| **ПІДГОТУВАВ:** | |
| **ДАТА:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.