

Характеристики



Eaton 195129

Eaton Moeller series xPole - HNB RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB C, 25A, 1p+N, , 30mA,

Загальні характеристики

PRODUCT NAME	Eaton Moeller series xPole - HNB RCBO - residual-current circuit breaker with overcurrent protection
---------------------	--

CATALOG NUMBER	195129
-----------------------	--------

EAN	9010238060920
------------	---------------

PRODUCT LENGTH/DEPTH	80 mm
-----------------------------	-------

PRODUCT HEIGHT	73 mm
-----------------------	-------

PRODUCT WIDTH	35 mm
----------------------	-------

PRODUCT WEIGHT	0.203 kg
-----------------------	----------

COMPLIANCES	CE Marked RoHS conform
--------------------	---------------------------

CERTIFICATIONS	CE
-----------------------	----

MODEL CODE	HNB-C25/1N/003
-------------------	----------------

Додаткова інформація

CURRENT LIMITING CLASS	3
------------------------	---

FEATURES	Concurrently switching N-neutral
----------	----------------------------------

Перевірка відповідності проектним вимогам згідно зі стандартом IEC/EN 61439 — технічні дані

AMBIENT OPERATING TEMPERATURE - MAX	40 °C
-------------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
-------------------------------------	--------

Програма доставки

AMPERAGE RATING	25 A
-----------------	------

FAULT CURRENT RATING	0.03 A
----------------------	--------

NUMBER OF POLES (PROTECTED)	1
-----------------------------	---

NUMBER OF POLES (TOTAL)	2
-------------------------	---

RATED CURRENT	25 A
---------------	------

RELEASE CHARACTERISTIC	C
------------------------	---

TYPE	RCBO
------	------

Technical data - electrical

DISCONNECTION CHARACTERISTIC	Undelayed
------------------------------	-----------

FREQUENCY RATING	50 Hz
------------------	-------

LEAKAGE CURRENT TYPE	AC
----------------------	----

POLLUTION DEGREE	2
------------------	---

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
--	------

RATED INSULATION VOLTAGE (UI)	500 V
-------------------------------	-------

RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
--------------------------------------	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60947-2)	0 kA
--	------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009-1)	6 kA
--	------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009)	6 kA
--	------

SURGE CURRENT CAPACITY	0.25 kA
------------------------	---------

VOLTAGE RATING	230 V
----------------	-------

VOLTAGE TYPE	AC
--------------	----

Technical data - mechanical

BUILT-IN DEPTH 69.5 mm

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MAX** 25 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MIN** 1 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MAX** 25 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MIN** 1 mm²

DEGREE OF PROTECTION IP20

MOUNTING METHOD DIN rail

**WIDTH IN NUMBER OF
MODULAR SPACINGS** 2

Ресурси

CHARACTERISTIC CURVE [eaton-xpole-hnb-characteristic-curve-004.jpg](#)

PEP ECO-PASSPORT [eaton-rcd-with-overcurrent-protection-pep-eato-00114-v0101-en.pdf](#)

БРОШУРИ [eaton-xPole-home-leaflet-br003019en-en-gb.pdf](#)

КАТАЛОГИ [eaton-xpole%20home-hnb-hx-rcbo-catalog-ca019023en-en-us.pdf](#)

[eaton-xpole-pkn6-m-dimensions.jpg](#)

КРЕСЛЕННЯ [eaton-xeffect-frbm6m-wiring-diagram.jpg](#)

[eaton-xpole-pkn6-m-3d-drawing.jpg](#)

НАЗВА ПРОЕКТУ:

НОМЕР ПРОЕКТУ:

ПІДГОТУВАВ:

ДАТА:



Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

