Характеристики



Eaton 248853

Eaton Z-SCH Installation contactor, 230VAC/50Hz, 2N/O+2N/C, 40A, 3HP

Загальні характеристики	
PRODUCT NAME	Eaton Z-SCH contactor
CATALOG NUMBER	248853
EAN	4015082488536
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	60 mm
PRODUCT WIDTH	52.5 mm
PRODUCT WEIGHT	0.36 kg
COMPLIANCES	RoHS conform
MODEL CODE	Z-SCH230/40-22

Powering Business Worldwide

Характеристики продукту

AMPERAGE RATING	40 A
FEATURES	Additional equipment possible
DEGREE OF PROTECTION	IP40
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	8.6 W
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-40 °C
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
INCANDESCENT LAMP LOAD - MAX	5520 W
LOAD FLUORESCENT LAMP - MAX	2610 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	5336 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	2088 VA
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	2
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	2
NUMBER OF MODULAR SPACINGS	3
RATED OPERATING VOLTAGE (UE) - MAX	440 V
RATED OPERATING VOLTAGE (UE) - MIN	440 V
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	40 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
UTILITY CATEGORY	1
VOLTAGE RATING (EXCITATION) - MAX	253 V
VOLTAGE RATING (EXCITATION) - MIN	195.5 V

Ресурси

КРЕСЛЕННЯ	eaton-3d-drawing-z-r-sch-einbau.jpg eaton-wiring-diagram-z-sch-klem-bez4.jpg eaton-3d-drawing-sch-pack.jpg eaton-mcb-dimensions-122x144.eps 122I169 eaton-dimensions-ma-sch40.jpg

BUILT-IN DEPTH	60 mm
VOLTAGE TYPE	AC
UTILIZATION CATEGORY (ACCORDING TO EN IEC 60947-4-1)	AC-1

НАЗВА ПРОЕКТУ:	
НОМЕР ПРОЕКТУ:	
ПІДГОТУВАВ:	
ДАТА:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.