

Характеристики



Eaton 031882

Eaton Moeller® series ETR4 Timing relay, 1W, 0.05s-100h, 24-240V50/60Hz, 24-240VDC, on-delayed

Загальні характеристики

PRODUCT NAME	Eaton Moeller® series ETR4 Timing relay
CATALOG NUMBER	031882
EAN	4015080318828
PRODUCT LENGTH/DEPTH	103 mm
PRODUCT HEIGHT	82 mm
PRODUCT WIDTH	23 mm
PRODUCT WEIGHT	0.109 kg
CERTIFICATIONS	UL File No.: E29184 Standard IEC/EN 61812 CSA CSA-22.2 No. 14 UL VDE 0435 CE CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA File No.: 012528 IEC/EN 61000-4-2 UL 508 IEC/EN 60947-5-1 IEC/EN 61000-4-3 IEC/EN 61812-1
MODEL CODE	ETR4-11-A



Powering Business Worldwide

Кліматичні умови середовища

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	45 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT STORAGE TEMPERATURE - MIN	45 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Перевірка конструкції

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.4 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.8 W

Електричний параметр

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
MAINS VOLTAGE TOLERANCE	24 - 240 V AC (at 50/60 Hz) 24 – 240 V DC
NOMINAL CURRENT	3 A
RATED BREAKING CAPACITY	3 A at AC-14 ($\cos \phi = 0.3$ 440 V) 1.1 x I _e (DC-11 L/R - 40 ms) 3 A at AC-15 ($\cos \phi = 0.3$ 220 V)
RATED FREQUENCY - MAX	63 Hz
RATED FREQUENCY - MIN	47 Hz
RATED MAKING CAPACITY	1.1 x I _e (DC-11 L/R - 40 ms) 50 A (AC-15 $\cos \phi = 0.3$ 220 V) 48 A (AC-14 $\cos \phi = 0.3$ 400 V)
RATED OPERATIONAL CURRENT (IE)	3 A at AC-14, 440 V 3 A at AC-14, 380 V 400 V 415 V 1.5 A at DC-11, 24 V 3 A at AC-15, 380 V 400 V 415 V 1.2 A at DC-11, L/R max. 50 ms 3 A at AC-15, 300 V 3 A at AC-15, 220 V 230 V 240 V 3 A at AC-14, 300 V (NC)
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	440 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	240 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V
SAFE ISOLATION	250 V AC, Between auxiliary contacts, According to EN 61140 250 V AC, Between coil and auxiliary contacts, According to EN 61140
SHORT-CIRCUIT PROTECTION RATING	Max. 6 A gG/gL, Fuse, Short-circuit rating without

Електромагнітна сумісність

AIR DISCHARGE	8 kV
BURST IMPULSE	1 kV, Signal cable According to IEC/EN 61000-4-4 2 kV, Supply cable
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	10 V/m at 80 - 1000 MHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 55011, conducted) Class B (EN 55011, radiated)
SURGE RATING	4 kV, asymmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, symmetrical, power pulses (Surge), EMC

welding, Contacts
Max. 6 A gG/gL, fuse,
Without welding, Contacts

Features & functions

ELECTRIC CONNECTION TYPE

Screw connection

FUNCTIONS

Fixed timing function
On-delayed
Delay-on energization

Загальні відомості

DEGREE OF PROTECTION

Terminals: IP20
IP20

LIFESPAN, MECHANICAL

30,000,000 Operations (DC
operated)
30,000,000 Operations (AC
operated)

MOUNTING POSITION

As required

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)

1

OVERVOLTAGE CATEGORY

III

POLLUTION DEGREE

2

PRODUCT CATEGORY

ETR4 timing relays

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC
4000 V AC

SHOCK RESISTANCE

4 g, Make contact,
Mechanical, according to
IEC/EN 60068-2-27, Half-
sinusoidal shock 20 ms

SUITABLE FOR

DIN rail (top hat rail)
mounting

TERMINAL CAPACITY

2 x (0.5 - 1.5) mm², flexible
with ferrule
1 x (20 - 14) AWG, solid or
stranded
2 x (0.5 - 1.5) mm², solid
1 x (0.5 - 2.5) mm², solid
1 x (0.5 - 2.5) mm², flexible
with ferrule

TIME RANGE - MAX

360000 s

TIME RANGE - MIN

0.05 s

TYPE

Timer relay

VOLTAGE TYPE

AC/DC

Магнітна система

COMMAND TIME	50 ms, AC 30 ms, DC
CONTACT CHANGEOVER TIME	4 ms
DUTY FACTOR	100 %
OPERATING FREQUENCY	4000 Operations/h
PICK-UP VOLTAGE	0.85 - 1.1 V AC x U_c 0.7 - 1.1 V DC x U_c
POWER CONSUMPTION	2 VA at AC (Sealing power) 2 VA at AC (Pick-up power) 1.8 W at DC (Sealing power) 1.8 W at DC (Pick-up power)
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
RECOVERY TIME	70 ms (after 100 % time delay)
REPETITION ACCURACY	≤ 0.5 % (deviation)
VOLTAGE TOLERANCE	0.85 x U_c , AC operated min. 1.1 x U_c , DC operated max. 0.7 x U_c , DC operated min. 1.1 x U_c , AC operated max.

Ресурси

CHARACTERISTIC CURVE	eaton-timers-diagram-etr4-timing-relay-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-timing-relay-declaration-of-conformity-uk250986en.pdf
БРОШУРИ	EMR6 - EMT6 - ETR4 brochure
ЕЛЕКТРИЧНА СХЕМА	eaton-timers-timing-relay-wiring-diagram.eps eaton-electronic-timers-relay-etr4-timing-relay-dimensions.eps eaton-timers-contactor-etr4-timing-relay-dimensions.eps eaton-general-m22-symbol.eps eaton-electronic-timers-relay-etr4-timing-relay-3d-drawing.eps
КРЕСЛЕННЯ	

НАЗВА ПРОЕКТУ:

НОМЕР ПРОЕКТУ:

ПІДГОТУВАВ:

ДАТА:



Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

