

Характеристики



Фото репрезентативне

Eaton 263467

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Turn-to-release function, Red, yellow, RAL 3000

Загальні характеристики

PRODUCT NAME	Eaton Moeller® series M22 emergency stop/emergency switching off pushbutton
CATALOG NUMBER	263467
EAN	4015082634674
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	70 mm
PRODUCT WIDTH	38 mm
PRODUCT WEIGHT	0.045 kg
COMPLIANCES	CE Marked UL 508 IEC 60947-5 EN 60947-5 CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 VDE CSA CSA File No.: 012528 CSA-C22.2 No. 94-91 UL UL Category Control No.: NKCR VDE 0660 CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 IEC/EN 60947-5 CE IEC/EN 60947 UL File No.: E29184 DNV GL LR
CERTIFICATIONS	
CATALOG NOTES	Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11



Powering Business Worldwide

MODEL CODE	M22-PVT
------------	---------

Контакти	
FORCE FOR POSITIVE OPENING - MIN	0 N

Зв'язок	
CONNECTION TO SMARTWIRE-DT	No

Виконавчий елемент	
ACTUATING FORCE	50 N
ACTUATOR COLOR	Red
ACTUATOR DIAMETER	38 mm
ACTUATOR FUNCTION	Turn-to-release Switching function latching
COLOR	Red
DESIGN	Mushroom-shaped Classical
ILLUMINATION	Non-illuminated
UNLOCKING METHOD	Turn-release

Кліматичні умови середовища	
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Перевірка конструкції

10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Features & functions

BASE COLOR	Yellow
BEZEL COLOR	Other
BEZEL MATERIAL	Other
DESIGN	Mushroom-shaped Classical
FEATURES	Tamper-proof (according to ISO 13850, EN 418)
RAL-NUMBER	3000

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Загальні відомості	
DEGREE OF PROTECTION	IP67/IP69K NEMA 4X, 13
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	As required
OPENING DIAMETER	22.5 mm
OPERATING FREQUENCY	600 Operations/h
PRODUCT CATEGORY	RMQ-Titan
SIZE	Front dimensions: 35 mm
SUITABLE FOR	Emergency stop
TYPE	Controlled stop pushbutton/emergency-stop button

Ресурси	
DECLARATIONS OF CONFORMITY	eaton-emergency-stop-emergency-switching-off-pushbutton-declaration-of-conformity-uk251132en.pdf
PEP ECO-PASSPORT	eaton-front-element-for-mushroom-pushbuttons-pep-eato-00328-v0101-en.pdf
ІНСТРУКЦІЇ ЩОДО ВСТАНОВЛЕННЯ	IL04716002Z IL04716005Z.pdf
КРЕСЛЕННЯ	eaton-operating-emergency-m22-dimensions.eps eaton-operating-emergency-m22-dimensions-002.eps eaton-operating-button-symbol-006.eps

[eaton-general-standards-000Z425.jpg](#)

[eaton-operating-button-symbol.eps](#)

[eaton-general-m22-standards.eps](#)

[eaton-operating-emergency-m22-3d-drawing-003.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

[eaton-operating-m22-3d-drawing.eps](#)

[eaton-general-m22-symbol.eps](#)

НАЗВА ПРОЕКТУ:

НОМЕР ПРОЕКТУ:

ПІДГОТУВАВ:

ДАТА:



Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

