

Product datasheet

uvex 2 trend 6934 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3 FO SR

Sizes: 35 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole with 5% recycled PU granulate from residues
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES		
Upper material	• hydrophobic leather • water-repellent (WPA)	
Lining material	• textile distance mesh lining for comfortable foot climate (clima zone)	
Fastening	• laces	
Reflecting elements	• for increased visibility even in dark working environments	
Comfort	• soft padding on collar • sizes 35-40 have been produced using a women's last • dust tongue	
Innersole	• removable comfortable innersole	
PROTECTIVE FEATURES		
Toe cap	• steel protective toe cap	
Penetration resistance	• steel penetration resistance	
Scuffcap	• out of PU for additional protection of the upper material	
CERTIFICATES		
uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191	
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1	
PRODUCT INFORMATION		
Product Information	• free from harmful substances in accordance with the uvex restricted substances list • detailed information on material composition and recycled content can be found in the uvex catalogue	
ACCESSORIES/ SPARE PARTS		
Replacement innersole	• 9518 7-9	
Laces	• black 8446022	
Semi-orthopaedic innersoles	tune-up • low: 95287 • medium: 95288 • high: 95289	SECOSOL® COMPLETE+ • low: 94790 • medium: 94791 • high: 94792