

Product datasheet

uvex 2 6503 1-4

Safety boot DIN EN ISO 20345:2022+A1:2024 S3L FO LG SC SR
 Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• hydrophobic leather • water-repellent (WPA)
Lining material	• textile distance mesh lining for comfortable foot climate (clima zone)
Fastening	• laces
Heel basket	• foamed PU heel basket for additional stability in the shoe
Reflecting elements	• for increased visibility even in dark working environments
Comfort	• soft padding on collar • sizes 35-40 have been produced using a women's last • dust tongue
Innersole	• removable comfortable innersole
Furthermore	• metal-free

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Penetration resistance	• metal-free, textile penetration resistance
Scuffcap	• out of PU for additional protection of the upper material (SC)
Ladder grip	• support on ladders due to transversely inserted profile (LG)

CERTIFICATES

uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

CARBON FOOTPRINT & PRODUCT INFORMATION

CO ₂ footprint	• 15.60 kg Cradle-to-Customer • 17.95 kg Cradle-to-Grave (calculation date 06/2025)
Product Information	• free from harmful substances in accordance with the uvex restricted substances list • detailed information on material composition and recycled content can be found in the uvex catalogue

ACCESSORIES/ SPARE PARTS

Replacement innersole	• 9534 7-0	
Laces	• black 9599921	
Semi-orthopaedic innersoles	tune-up • low: 95281 • medium: 95282 • high: 95283	SECOSOL® COMPLETE+ • low: 94790 • medium: 94791 • high: 94792