

Product datasheet

uvex 2 allround 8595 3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3L FO LG SC SR
Sizes: 35 - 50 | Width: 11



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)

FEATURES

Upper material	• leather
Lining material	• water repellent (WPA)
Fastening	• textile distance mesh lining for comfortable foot climate
Comfort	• laces
Insock	• soft padding on collar
	• comfortable innersole

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Penetration resistance	• metal-free, textile penetration resistance (tested with 4,5 mm test nail)
Scuffcap	• out of PU for additional protection of the upper material (SC)
Ladder grip	• support on ladders due to transversely inserted profile (LG)

CERTIFICATES

ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
-----	--

SUSTAINABILITY

CO2 footprint	• 20.49 kg Cradle-to-Customer
	• 22.90 kg Cradle-to-Grave (calculation date 06/25)
Recycled/sustainable materials	• removable insock made wholly or partly from recycled materials
	• free from harmful substances in accordance with the uvex restricted substances list

ACCESSORIES/ SPARE PARTS

Laces	• black 9599920
-------	-----------------