

Home energy storage Battery (wall-mounted)

LFELI-48200W2

Product Introduction

LFELI-48200 is an energy storage module based on a home wall-mounted design. The system uses distributed photovoltaic and wind power generation to provide a household power supply solution. It can effectively realize energy transformation and storage, solve the imbalance between distributed generation and load, improve the stability and utilization rate of renewable energy generation, realize "spontaneous self-use" at the user end, and save electricity costs. The system uses high-efficiency and long-life lithium iron phosphate batteries, and the excellent battery management system can ensure its life of more than 15 years.

Characteristics

- ◆ High energy density and conversion efficiency
- ◆ Intelligent software anti-theft design
- ◆ Compatible with many inverters
- ◆ Easy maintenance with SOC (charge status) and SOH (health status) detection



Specification

Items		Parameters
basic parameter	Specifications and models	LFELI-48200W2
	Nominal voltage	51.2 V
	Nominal capacity	200Ah @ 0.2C, 25°C
	Maximum continuous charge/discharge current	100A/200A @ 25°C
	Maximum charge/discharge voltage	57.6 V/43.2 V
	Weight	About. 91kg
	Dimensions(W×D×H) (inch)	500mm×620mm×245mm (19.69*24.41*9.65)
	Cycle life	5000 cycles @ 25°C 80% DOD
	Number of parallel connections supported	16
	Self-discharge (month)@25°C	≤3%
	BMS communication types	RS485; RS232; CAN
	Cooling Mode	Free cooling
	IP Class	IP32
	Display Fuction	Without
	Design Life	15 years
	Shell Material	Q235A
	Certification	CE UN38.3 UL IEC TUV

Items		Parameters
Environment	Storage Temperature	0°C to 40°C
	Transport Temperature	-20°C to 60°C
	Operate Temperature	charge:0°C to 45°C; discharge: -20°C to 60°C (45°C Load reduced)
	Relative Humidity	5% to 95%
	Working Pressure	61kPa~113kPa

Note: The battery should be stored according to storage requirements, the best storage temperature is 20°C -30°C ; Complete charge and discharge once every 3 months and recharge to 70% of the capacity.

Discharging Diagram					
Time (h)	1h	2h	3h	5h	10h
Constant Current (A)	200A	100A	66A	40A	20A
Constant Power (W)	10240W	5120W	3379W	2048W	1024W

Life curve

Cycle life curve under different DOD and temprature conditions

