G Non-Electric Automatic Water Filtering Valve



Jkmatic JKMATIC CO., LTD.

RESPONSIBILITY INTEGRITY PURPOSE PRINCIPLE

Service Line: 0086-10-69730336 Email: jk@kangjiezc.com Website: www.kangjiezc.com Address: No.5 Huaiying Street, Shahe Industrial Zone, Changping District, Beijing, China 102206



Net Weight：1.8Kg

Working pressure：0.2-0.6Mpa　Riser Tube OD：26.7/32mm　Working temperature：4-40°C

Outlet pressure：⩾0.15Mpa　Material：NORYL　Filtration steps：Backwash+Rinse

It's the non-electric control valve which is specially for multiple-media filtration process with multiple patented technologies, it's suitable for commercial and domestic applications.

PRODUCT FEATURE

1. Unique hydraulic powered mechanism, fully auto switchover. No electric required. Energy saving and eliminate electrical hazards.
2. Large diameter drain channel, with good backwash effect.
3. Features: Manual Force Regen Knob, press the button to start the backwash process.
4. It's suitable for multiple-media automatic filter.
5. "Fool proof", simple and practical operation. Not require complicated setting and adjustment.
6. The six kinds of water meter disc is suit for difference water quality.

PERIODIC WATER PRODUCTION

Model		G1.0	G2.0	G3.0	G1.1	G2.1	G3.1
Backwash Duration（min）		5			15		
Recommended Tank Size		6"/7"/8"	9"/10"/12"	12"/14"	6"/7"/8"	9"/10"/12"	12"/14"/16"
Service Flow Rate（m^3/h）		0.5～1.0	1.0～2.0	2.0～3.0	0.5～1.0	1.0～2.0	2.0～3.0
Recommended Water Production/cycle（m^3）	1# Water Meter	12			12		
	2# Water Meter	6			6		
	3# Water Meter	4			4		
	4# Water Meter*	3			3		
	6# Water Meter	2			2		
	8# Water Meter	1.5			1.5		
Drain Volume(L)		50	105	180	150	315	540

Service Line: 0086-10-69730336 Email: jk@kangjiezc.com Website: www.kangjiezc.com Address: No.5 Huaiying Street, Shahe Industrial Zone, Changping District, Beijing, China 102206