



UT380 SERIES

Luminometers

UT381 • UT382



UT381



UT382

SPECIFICATIONS

Basic Functions		Range	Best Accuracy	
			UT381	UT382
Illuminance Measurement	LUX	20 Lux	±(3%+20)	±(3%+20)
		200 Lux	±(3%+8)	±(3%+8)
		2000 Lux	±(3%+8)	±(3%+8)
		20000 Lux	±(3%+8)	±(3%+8)
Illuminance Measurement	CD	2CD		
		20CD		
		200CD		
		2000CD		
Special Functions				
Data Hold		Display "HOLD"	✓	✓
Illuminance Measurement		Display "Lux/CD"	✓	✓
Max / Min Mode		Display "MAX" or "MIN"	✓	✓
Sleep Mode		Around 10 minutes	✓	✓
Low Battery Indication		Around <7.1V	✓	✓
Data Logging			✓	✓
Auto Ranging			✓	✓
Real Time Clock			✓	✓
Working Temperature		0°C~40°C(32°F ~ 104°F)	✓	✓
Deposited Temperature		-10°C~55°C(14°F~122°F)	✓	✓
Relative Humidity		≤75%	✓	✓
USB				✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (6LF22)
LCD Size	22,5 x 32,5mm
Product Colour	Red and Grey
Product Net Weight	185g
Product Size	195 x 45 x 26mm
Standard Accessories	USB Interface Cable, CD (UT382 Only), English Manual, Carrying Bag, Battery
Standard Individual Packing	Blister
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	650 x 560 x 300 mm (0.1 ICBM Per Standard Carton)
Standard Carton Gross Weight	15kg