



UT15 SERIES

Waterproof Type Voltage Testers

UT15A · UT15B · UT15C



SPECIFICATIONS

Technical Functions / Features	UT15A	UT15B	UT15C
Voltage LED Steps (AC/D)	12V: between 0 to 12V LED will illuminate 24V: between 19V ± 2V LED will illuminate 50V: between 48V ± 6V LED will illuminate 120V: between 110V ± 20V LED will illuminate 230V: between 200V ± 20V LED will illuminate 400V: between 340V ± 30V LED will illuminate 690V: between 520V ± 30V LED will illuminate		
Continuity Test	Range 0 to 100kΩ. The continuity LED will illuminate and buzzer will sound		
Phase Rotation Test	50Hz to 60Hz	50Hz to 60Hz	50Hz to 60Hz
Range Selection	Automatic	Automatic	Automatic
Polarity Detection	Positive & Negative	Positive & Negative	Positive & Negative
Low Battery Indication	Short circuit Two Leads, LED function does not turn on when battery is low		
Torch	✓	✓	✓
Single Lead (L2) Voltage Detection	It is intended only as a quick check. 100V to 690V; 50Hz to 400Hz		
Short Circuit Detection		✓	✓
LCD Display (AC/DC)			24V to 690V: ±(3%+5)



UT15A



UT15B



UT15C

GENERAL CHARACTERISTICS

Power	1.5V Batteries (R03) × 2
LCD Size	UT15C- 23 × 12mm
Product Colour	Red and Grey
Product Net Weight	210g
Product Size	275 × 51 × 30mm
Standard Accessories	Batteries, English Manual
Standard Individual Packing	Blister
Standard Quantity Per Carton	30pcs
Standard Carton Measurement	440 × 295 × 455 mm (0,079CBM Per Standard Carton)
Standard Carton Gross Weight	17kg