

Glass Passivated Bridge Rectifiers

FEATURES

- Glass passivated junction
- Ideal for printed circuit board
- High case dielectric strength
- Typical IR less than 0.1μA
- High surge current capability
- UL Recognized File # E-326243
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



KBU



MECHANICAL DATA

Case: KBU

Molding compound, UL flammability classification rating 94V-0


Base P/N with suffix "G" on packing code - green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

Mounting torque: 0.56 Nm max.

Weight: 7.2 g (approximately)



| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted) | | | | | | | | | |
|--|--------------------------------------|--------------|----------|----------|----------|----------|----------|----------|------------------|
| PARAMETER | SYMBOL | KBU 601G | KBU 602G | KBU 603G | KBU 604G | KBU 605G | KBU 606G | KBU 607G | Unit |
| Maximum repetitive peak reverse voltage | V _{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum RMS voltage | V _{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Maximum DC blocking voltage | V _{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum average forward rectified current | I _{F(AV)} | 6 | | | | | | | A |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load | I _{FSM} | 175 | | | | | | | A |
| Rating for fusing (t<8.3ms) | I ² t | 127 | | | | | | | A ² s |
| Maximum instantaneous forward voltage (Note 1) I _F = 3 A I _F = 6 A | V _F | 1.0 1.1 | | | | | | | V |
| Maximum DC reverse current at rated DC blocking voltage T _J =25 °C T _J =125°C | I _R | 5 500 | | | | | | | μA |
| Typical junction capacitance per leg | C _j | 400 | | | | | | | pF |
| Typical thermal resistance | R _{θJC} R _{θJA} | 3.1 8.6 | | | | | | | °C/W |
| Operating junction temperature range | T _J | - 55 to +150 | | | | | | | °C |
| Storage temperature range | T _{STG} | - 55 to +150 | | | | | | | °C |

Note 1: Pulse Test with PW=300μs, 1% Duty Cycle

Note 2: Measured at 1MHz and applied Reverse Voltage of 4.0V D.C.

ORDERING INFORMATION

| PART NO. | PACKING CODE | PACKING CODE SUFFIX | PACKAGE | PACKING |
|---------------------|--------------|---------------------|---------|------------|
| KBU60xG (Note 1) | T0 | G | KBU | 500 / Tray |

Note 1: "x" defines voltage from 50V (KBU601G) to 1000V (KBU607G)

EXAMPLE

| PREFERRED P/N | PART NO. | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION |
|---------------|----------|--------------|---------------------|----------------|
| KBU607G T0 | KBU607G | T0 | | |
| KBU607G T0G | KBU607G | T0 | G | Green compound |

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

FIG. 1 MAXIMUM DERATING CURVE FOR OUTPUT CURRENT




FIG. 2 MAXIMUM FORWARD SURGE CURRENT PER LEG




FIG. 3 TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 4 TYPICAL FORWARD CHARACTERISTICS PER LEG






FIG. 5 TYPICAL JUNCTION CAPACITANCE



PACKAGE OUTLINE DIMENSIONS

KBU



| DIM. | Unit (mm) | | Unit (inch) | |
|------|------------|------|--------------|-------|
| | Min | Max | Min | Max |
| A | 18.8 | 19.8 | 0.740 | 0.780 |
| B | 4.6 | 5.6 | 0.181 | 0.220 |
| C | 8.2 (TYP.) | | 0.322 (TYP.) | |
| D | 1.2 | 1.3 | 0.047 | 0.051 |
| E | 20.0 | - | 0.787 | - |
| F | 6.8 | 7.1 | 0.268 | 0.280 |
| G | 22.7 | 23.7 | 0.894 | 0.933 |
| H | 4.6 | 5.0 | 0.181 | 0.197 |

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[KBU601G](#) [KBU602G](#) [KBU603G](#) [KBU604G](#) [KBU605G](#) [KBU606G](#) [KBU607G](#)