

21551 PE FOAM TAPE

Technical Data Sheet

Description

21551 is a double sided foam mounting tape which is designed for use in permanent bonding, fixing and mounting applications to various substrates, such as PVC, glass, wood and metal.

Adhesive

- Synthetic rubber

Carrier

- 3,00 mm polyethylene foam
- Density: 67 kg/m³
- White

Liner

- Siliconized paper
- Brown

Applications

Industry:

- Point of sale display applications
- Mounting of panels
- Mounting exhibition materials

Technical details

Adhesive strength

25 N/25 mm

Shear adhesion

500 g/625 mm²

Service temperature range

-30°C to +80°C

UV resistance

Good

Ageing resistance

High

Usage

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_05022014 Version 03

