

32112 HIGH STRENGTH ACRYLIC

Technical Data Sheet

Description

32112 HSA is especially designed for permanent bonding in interior and exterior applications. This can replace riveting, welding, liquid glues and other permanent fasteners. It is also suitable for various kinds of substances, such as metal, wood, glass and many plastics.

Adhesive

- Acrylic
- Excellent shear performance
- Pressure sensitive, providing high tack
- Density: 900 kg/m³
- Thickness: 0,50 mm
- Transparent

Carrier

- No carrier

Liner

- Low density polyethylene
- Red

Applications

Car

- Fixing exterior trims and bodyside mouldings
- Emblem, badge, mounting and rear view mountings
- Panel mounting

Industry

- Signs and panels
- Interior and exterior use

Technical details

Adhesion	31,9 N/25mm
Dynamic shear adhesion	5,5 kg/cm²
Temperature range	-30°C to +120°C
Solvent resistance	No degradation
UV resistance	Good
Moisture resistance	Excellent

Usage

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_14012013 Version 03

