

# 18209 TISSUE TAPE

## Technical Data Sheet

### Description

18209 is a double sided tissue tape consisting of a solvent acrylic adhesive. It is suitable for a wide range of applications.

### Adhesive

- Solvent acrylic

### Carrier

- Tissue

### Liner

- Siliconized paper  
- White

### Applications

- Suitable for general bonding, bag sealing, photo sticking, envelop sealing, foam laminating, etc.  
- Application of point-of-sales displays

### Technical details

#### Thickness

0,1 mm

#### Adhesive strength

18 N/25 mm

#### Tensile strength

40 N/25 mm

#### Service temperature range

-20°C to +100°C

#### Elongation

3,5%

### Usage

Temperature: between +10°C and +40°C. Surface must be clean, dry and free from dust, grease or oil. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23 °C.

### Storage and shelf life

Clean and dry in a well ventilated area, out of direct sunlight, preferably at a temperature between 21°C and 50% relative humidity. Stored under these conditions shelf life will be 12 months.

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*

Frankrijkstraat 8  
9140 Temse - Belgium  
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64  
info@optiontapespecialties.com - www.optiontapespecialties.com  
OTS\_05022014 Version 02

