

18151 DOUBLE SIDED CARPET TAPE

Technical Data Sheet

Product description

18151 is a double sided carpet tape, consisting of a polyester carrier and a hot melt rubber adhesive. This tape has strong adhesive and tensile properties. Especially designed for exhibitions.

Construction

- Adhesive	Hot melt rubber
- Carrier	Polyester
	White
- Liner	Siliconised paper
	Brown

Applications

- Suitable for most types of carpets
- Designed for carpet decorating, jointing and fixing
- Can be used for wall furnishing and metal jointing

Technical details

Thickness	0,25mm
Adhesive strength	13,9 N/25 mm
Tensile strength	75 N/25 mm
Service temperature range	-10°C up to +60°C

Recommendations for use

Temperature: between +10°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area out of direct sunlight, preferably at a temperature between +10°C and +23°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_27032014 Version 01

