

18220 DOUBLE SIDED REINFORCED TRANSFER TAPE

Technical Data Sheet

Description

18220 is a double sided reinforced transfer tape consisting of a fabric adhesive carrier and an acrylic dispersion. This tape offers a very high tack and is ideal as a carpet tape for interior use.

Adhesive

- Synthetic rubber

Carrier

- Fabric
- Transparent

Liner

- Siliconized paper
- Brown

Applications

- Application of floor coverings to most surfaces
- Permanent adhesion

Technical details

Thickness	0,22 mm
Adhesive strength	25 N/25 mm
Shear adhesion	500 g/625 mm ²
Service temperature range	-20°C to +80°C
Condensation resistance	High
Ageing resistance	Very high
Plasticiser resistance	High

Usage

Temperature: between +5°C and +30°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature at +23°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_05022014 Version 02

