

MADE IN TAIWAN

CMT7E

REMOVABLE PLUNGE SPRING

for easy bit adjustment when table mounted



ELECTRONIC SPEED CONTROL & SOFT START

From 8.000 - 20.000 RPM

SWITCHING FROM A PLUNGE TO A FIXED BASES ROUTER

with rack and pinion adjustment is as simple as turning a dial



QUICK ACCESS BRUSHES

allows the end user to change worn brushes



SAFETY SWITCH SHUTTER

locks closed in bit change mode to prevent power on

SIDE AIR VENTS

reduces intake of dust into the motor casing when mounted upside-down in a router table

3 STAGE TURRET

with direct reading scales for precise preset cut depths



TOP OF TABLE HEIGHT ADJUSTMENT



Top of table height adjustment is possible using the height winder handle from the template guide kit.



CMT7E-TGA

Template guide kit includes 7 guide bushes, guide plate, alignment bush, spacer



Optional CMT7E-TGA

Technical Specifications

- Horsepower 2.000 Watt
- No load speed 8.000-20.000 RPM
- Plunge stroke 0-68mm
- Collet diameter. Ø6-12,7mm
- Tool weight 6 Kg

Collets for CMT7E

- | | |
|------------|------------|
| 796.660.00 | D = 6mm |
| 796.664.00 | D = 6,35mm |
| 796.680.00 | D = 8mm |
| 796.700.00 | D = 10mm |
| 796.720.00 | D = 12mm |
| 796.727.00 | D = 12,7mm |



DESCRIPTION	ORDER NO.
Router complete with standard equipment	CMT7E