

## TECHNICAL DATA SHEET

**PRODUCT:** HPE3530

**GROUP:** HYDROWOOD WHITE TOPCOAT

### CHARACTERISTICS

White topcoat water-based, for application with spray gun, air mix, airless.  
Ideal for outdoor use.

### TECHNICAL SPECIFICATIONS

HPE3530	Density (20°C)	1,03 - 1,07	gr/cc	IST 11/01
	Viscosity Brookfield (20°C)	10000 - 11500	Cps	IST 11/05
	Solid content	38 - 45	%	IST 11/06

The values describe typical properties of the product, Technical Specifications are available on request.

### BINDER

Self-crosslinking acrylic copolymer emulsion

### THINNING

The product is ready to use. If thinning is required, add water in according with application method.

### APPLICATION

Thickness	Minimum 200 microns of wet film
Dust - Free	Estimated 90' - 120' at 25°C
Stackable	After 24 hours at 25°C
Opacity	27 - 36 Gloss

### PRECAUTIONS FOR STORAGE AND PACKING

To conserve in the original cans, tightly sealed, in a fresh atmosphere, not subject to abrupt thermal excursions (+5°C/+35°C). Standard packaging 25 Kg., for other specific requests, upon evaluation of availability.

### SAFETY PRECAUTIONS

The product is intended for professional use only, refer to the Safety Data Sheet.