







# Park Ranger 2150 Suction Sweeper

The Nilfisk-Egholm suction sweeper unit is the most effective choice for the maintenance sweeping on footpaths, pavements, car parks, stairwells etc. The sweeper unit features a fibreglass high tip hopper and a rotation cast fresh water tank. It is a robust and compact machine with low noise operation. Hopper discharge follows directly from the driver's seat.



The dust is fully under control with the Nilfisk-Egholm suction sweeper unit. Two spray jets mounted on the front brushes dampen the sweeping area and thereby bind the dust. The collecting tank features an innovative filter system binding even the smallest dust particles inside the tank.

The spiral brush almost feeds the swept material into the suction hose, which allows all sweepings a problem free passing to the collecting tank.



With the Park Ranger 2150 the changeover from one attachment to another is done in less than 4 minutes - no tools required!





# Technical data Suction Sweeper





1,200 mm

### **Special features**

Dust control: the hopper features an integrated self-cleaning filter system to prevent dust emissions

Vacuum — the material that the machine sweeps up does not come into contact with the turbine

Special vacuum nozzle with spiral brush

Speed regulation of the front brushes is standard

Nose wheel for height regulation of the front brushes — excellent sweeping result and minimal brush wear

Frame to assist fitting and removal of the hopper supplied

### Extra equipment

**External vacuum hose:** the external vacuum hose is ideal for cleaning hard-to-reach places such as between parked bicycles or in stairwells. The 6-metre-long hose is stored on top of the hopper and is always ready to use.

**Third side brush:** Extends the sweeping width to 1,660 mm. This brush is operated hydraulically, which makes it perfect for sweeping right up to house walls or under benches, for example.



### **Dimensions**

# Attached:

Length	2,900 mm
Width	1,200 mm
Height without cab	1,850 mm
Height with cab	1,935 mm
Height with remote vac hose	2,200 mm

# **Storage dimensions:**

Length	1,350 mm
Width	1,010 mm
Height	1,920 mm

### Technical data:

recinical data.	
Weight - hopper	135 kg
Weight- front brushes	50 kg
Weight - container frame	30 kg
Max. weight in hopper	300 kg
Hopper volume	450 L
Water tank volume	100 L
Clearing width with two brushes	1,200 mm
Clearing width with three brushes	1,660 mm
Air speed	140 km/h
Airflow	2,500 m <sup>3</sup> /h
Turbine diameter	500 mm
Tipping height	1,300 mm
Ground clearance below vacuum nozzle	55 mm
Ground clearance below brushes	140 mm
Cound levels according to	

Sound levels according to

EU directive 2000/14 LwA 107 dB(A)

## **CE certified according to EU Directive**

## Nilfisk-Egholm A/S

Transportvej 27 DK-7620 Lemvig T. +45 97 81 12 05

F. +45 97 81 12 10

www.nilfisk-egholm.com

info@egholm.dk