



City Ranger 2200 Snow V-Blade

When heavy and icy snow covers the ground, you need the snow v-blade close at hand. It uses the tip of the 'V' to cut through heavy and encrusted snow, separating and pushing it to both sides. Even large amounts of snow are removed with ease.



The v-blade can also be configured as a 'Y' to allow snow to be transported away – very useful in car parks, markets, enclosed courtyards and other locations where snow needs to be gathered in one place.

Soft ground? No problem

The snow v-blade always follows the terrain, whether soft, hard or uneven. The ability to distribute weight to the basic machine even allows the snow v-blade to clear gravel paths, as the reduced weight prevents it from digging into the gravel. The snow v-blade height can also be adjusted to cater for uneven pavements and low curbs.

Dual efficiency

The combination of the quick-working snow v-blade at the front and the salt and sand spreader at the back of the basic machine means that snow clearing and salting are completed in a single pass – on snow up to 50 cm thick and 1.2–1.4 metres wide.

As well as being extremely efficient, the snow v-blade is also very quiet and comfortable to operate.



When you change attachments, the City Ranger 2200 hydraulic hoses are connected at the turn of a handle!



**Nilfisk
Egholm**
Rangers at heart

Technical data

Snow V-Blade



Special features

- Handles snow up to 50 cm thick
- Clearing width 1.2–1.4 m
- Both blades hydraulically-adjusted
- A-frame featuring integrated vibration damping – Quiet and comfortable
- Steel blades as standard
- Safety tilt system
- Well suited to gravel paths due to weight distribution to basic machine
- 2 skids for height adjustment - uneven pavements and low curbs require e.g. high adjustment
- Lateral floating position – skid and blade follow the terrain
- Often used in combination with the Salt and Sand Spreader

Extra equipment

- Rubber scraping edge for surfaces that require extra care

Dimensions

Fitted:

Length	3,000 mm
Width	1,400 mm
Height	1,960 mm

Storage dimensions:

Length	500 mm
Width	1,400 mm
Height	600 mm

Technical data:

Weight	118 kg
Clearing width	1,300–1,400 mm
Ground clearance under scraper	240 mm
Ground clearance under support strut	215 mm

CE certified according to EU Directive

Nilfisk-Egholm A/S

Transportvej 27

DK-7620 Lemvig

T. +45 97 81 12 05

F. +45 97 81 12 10

www.nilfisk-egholm.com

info@egholm.dk