



## Park Ranger 2150 Tipper trailer

*The tipper trailer is tailor-made for your Park Ranger, and provides for efficient transportation of sand, soil and park and garden waste to and from park areas. Easy manoeuvrability allows you to transport the load to the exact location where it will be used, and good weight distribution ensures no tracks will be left in the lawn afterwards.*

The tipper trailer has a load capacity of 300 kg, and offers great flexibility – the top section of each side can be removed, and the back flap can be dropped fully down. The trailer can be emptied from the driver's seat using the hydraulic tipping function.



The tipper trailer also serves as the base for the leaf hopper on the leaf suction unit (see the datasheet for the leaf suction unit).



*With the Park Ranger 2150 the changeover from one attachment to another is done in less than 4 minutes - no tools required!*



# Technical Data Tipper trailer



## Special features

The tipper trailer has a strong steel chassis with removable sides

The back flap can be locked in the horizontal position, to allow for the transportation of planks, garden tools, etc

The tipper trailer has a load capacity of 300 kg

The hydraulic tipping action makes it fast and easy to empty the tipper trailer

The supplied frame allows for simple and rapid fitting and removal of the tipper trailer. One person can therefore easily attach the tipper trailer alone

## Dimensions

### Attached:

Length	2,440 mm
Width	1,015 mm
Height	1,935 mm

### Storage dimensions:

Length	1,400 mm
Width	950 mm
Height	1,350 mm

### Internal trailer dimensions:

Length	1,040 mm
Width	860 mm
Height	300/600 mm

### Technical data:

Unladen weight	100 kg
Load capacity	300 kg
Volume	0.4 m <sup>3</sup>

CE certified according to EU Directive

## Nilfisk-Egholm A/S

Transportvej 27

DK-7620 Lemvig

T. +45 97 81 12 05

F. +45 97 81 12 10

[www.nilfisk-egholm.com](http://www.nilfisk-egholm.com)

[info@egholm.dk](mailto:info@egholm.dk)